



Technical Data Sheet

SIZES Body	24 X 48 IN. Rectified Porcelain		24 X 24 IN. Rectified Porcelain		12 X 24 IN. Rectified Porcelain		9 X 10 IN. (Hex) Pressed Porcelain	3 X 12 IN. Pressed Ceramic	
	Polished	Matte	Polished	Matte	Polished	Matte	Matte	Glossy	Matte
	✓	✓	✓	✓	✓	✓	✓	✓	✓
	15 Faces		30 Faces		60 Faces		10 Faces	10 Faces	

Technical Specs.

PORCELAIN		
	Grout size	1/12"
	P.E.I.	4 (Medium - Heavy Traffic)
	Shade and Texture Mixture	High
	Chemical Resistance	Compliant A.S.T.M. C650
	DCOF	≥ 0.42 A.S.T.M. C1028
	Water absorption	≤ 0.5 % A.S.T.M. C373
	MOHS	5 - 8 A.S.T.M. C1028
	Breaking Strength	≥ 771 lbs. ISO 10545-4
	Thermal Shock Resistance	Compliant A.S.T.M. C484
	Frost Resistance	Compliant A.S.T.M. C1026
	Stain Resistance	Compliant A.S.T.M. C1378
	Abrasion Resistance	Compliant ANSI A137

CERAMIC		
	Grout size	1/6"
	Shade and Texture Mixture	High
	Chemical Resistance	Compliant A.S.T.M. C650
	Water absorption	≤ 20 % A.S.T.M. C373
	MOHS	5 - 8 A.S.T.M. C1028
	Thermal Shock Resistance	Compliant A.S.T.M. C484
	Resistance to Cracking	Compliant A.S.T.M. C1026
	Stain Resistance	Compliant A.S.T.M. C1378

Packaging Information

SIZE	Pcs./Box	Sq.ft./Box	Lbs./Box		Box/PAL	Sq.ft./PAL	Lbs./PAL	
			POLISHED	MATTE			POLISHED	MATTE
24 X 48 IN.	2	15.50	64.50	62.25	40	620	2,652.02	2,683.06
24 X 24 IN.	4	15.50	65.16		36	558	2,369.9	
12 X 24 IN.	8	15.50	65.74		48	744	3,348.6	
9 X 10 IN.	18	9.08	33.84		65	590.07	2,278.9	
3 X 12 IN.	22	5.33	15.65		132	703.56	2,111.4	

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.



Ficha Técnica

FORMATOS Pasta	60 X 120 CM. Porcelánico Rectificado		60 X 60 CM. Porcelánico Rectificado		30 X 60 CM. Porcelánico Rectificado		23.2 X 26.7 CM (Hex) Porcelánico Prensado	7.5 X 30 CM. Cerámico Prensado		
	Color / Acabado	Pulido	Mate	Pulido	Mate	Pulido	Mate	Mate	Brillante	Mate
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	15 Caras		30 Caras		60 Caras		10 Caras	10 Caras		

Información Técnica

PORCELÁNICO

	Separación de boquilla	2 mm	
	P.E.I.	4 (Tráfico: Medio - Alto)	
	Tono y Textura Mezclado	Alto	
	Resistencia al ataque químico	Conforme	A.S.T.M. C650
	Coefficiente Dinámico de Fricción	≥ 0.42	A.S.T.M. C1028
	Absorción de agua	≤ 0.5 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia a la flexión	≥ 350 kg	ISO 10545-4
	Resistencia al shock térmico	Conforme	A.S.T.M. C484
	Resistencia a helada	Conforme	A.S.T.M. C1026
	Resistencia a las manchas	Conforme	A.S.T.M. C1378
	Resistencia a la abrasión	Conforme	ANSI A137

CERÁMICO

	Separación de boquilla	4 mm	
	Tono y Textura Mezclado	Alto	
	Resistencia al ataque químico	Conforme	A.S.T.M. C650
	Absorción de agua	≤ 20 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia al shock térmico	Conforme	A.S.T.M. C484
	Resistencia al craquel	Conforme	A.S.T.M. C1026
	Resistencia a las manchas	Conforme	A.S.T.M. C1378

Información de Embalaje

FORMATO	Pzs./Caja	m2/Caja	Kg./Caja		Caja/Tarima	m2/Tarima	Kg./Tarima	
			PULIDO	MATE			PULIDO	MATE
60 X 120 CM	2	1.44	29.05	29.50	40	57.6	1,203.3	1,217.3
60 X 60 CM	4	1.44	29.35		36	51.84	1,075.0	
30 X 60 CM	8	1.44	31.25		48	69.12	1,518.9	
23.2 X 26.7 CM	18	0.84	15.50		65	54.6	1,033.7	
7.5 X 30 CM	22	0.49	7.1		132	64.68	957.7	