



## Technical Data Sheet

SIZES Body	32 X 64 IN. Rectified Porcelain		32 X 32 IN. Rectified Porcelain	
	Polished	Matte	Polished	Matte
		✓		✓
	8 Faces		16 Faces	

## Technical Specs.

PORCELAIN			
	Grout size	1/12"	
	P.E.I.	4 (Medium - Heavy Traffic)	
	Shade and Texture Mixture	High	
	Chemical Resistance	Compliant	A.S.T.M. C650
	DCOF	≥ 0.42 Interior Dry (ID)	ANSI A326.3 - 2021
	Water absorption	≤ 0.5 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Breaking Strength	≥ 771 lbs.	ISO 10545-4
	Thermal Shock Resistance	Compliant	A.S.T.M. C484
	Frost Resistance	Compliant	A.S.T.M. C1026
	Stain Resistance	Compliant	A.S.T.M. C1378
	Abrasion Resistance	Compliant	ANSI A137

## Packaging Information

SIZE	Pcs./Box	Sq.ft./Box	Lbs./Box	Box/PAL	Sq.ft./PAL	Lbs./PAL
32 X 64 IN.	2	27.55	131.5	24	661.20	3,217.4
32 X 32 IN.	3	20.67	86.8	32	661.44	3,158.3

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.



## Ficha Técnica

FORMATOS Pasta	80 X 160 CM Porcelánico Rectificado		80 X 80 CM Porcelánico Rectificado		
	Color / Acabado	Pulido	Mate	Pulido	Mate
			✓		✓
	8 Caras		16 Caras		

## Información Técnica

### PORCELÁNICO

	Separación de boquilla	2 mm	
	P.E.I.	4 (Tráfico: - Alto)	
	Tono y Textura Mezclado	Alto	
	Resistencia al ataque químico	Conforme	A.S.T.M. C650
	Coefficiente Dinámico de Fricción	≥ 0.42 Interior Seco	ANSI A326.3 - 2021
	Absorción de agua	≤ 0.5 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia a la flexión	≥ 350 kg	ISO 10545-4
	Resistencia al shock térmico	Conforme	A.S.T.M. C484
	Resistencia a helada	Conforme	A.S.T.M. C1026
	Resistencia a las manchas	Conforme	A.S.T.M. C1378
	Resistencia a la abrasión	Conforme	ANSI A137

## Información de Embalaje

FORMATOS	Pzs./Caja	m2/Caja	Kg./Caja	Caja/Tarima	m2/Tarima	Kg./Tarima
80 X 160 CM	2	2.56	59.65	24	61.44	1,459.4
80 X 80 CM	3	1.92	43.95	32	61.44	1,432.6