
























Technical Data Sheet

SIZES Body	9 X 10 IN. (Hex) Pressed Porcelain		Faces
Color / Finish	Matte		
 White  Gray  Black	✓	10 Faces	
 Avalon  Nord	✓	4 Faces	
 Blue  Green  Rose  Tobacco	✓	16 Faces	

Technical Specs.

PORCELAIN			
	Grout size	1/6"	
	P.E.I.	4 (Medium - Heavy Traffic)	
	Shade and Texture Mixture	Low	
	Chemical Resistance	Compliant	A.S.T.M. C650
	DCOF	≥ 0.42 Interior Wet (IW)	ANSI A326.3 - 2021
	Water absorption	≤ 0.5 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Breaking Strength	≥ 771 lbs.	ISO 10545-4
	Thermal Shock Resistance	Compliant	A.S.T.M. C484
	Frost Resistance	Compliant	A.S.T.M. C1026
	Stain Resistance	Compliant	A.S.T.M. C1378
	Abrasion Resistance	Compliant	ANSI A137










Packaging Information

SIZE	Pcs./Box	Sq.ft./Box	Lbs./Box	Box/PAL	Sq.ft./PAL	Lbs./PAL
9 X 10 IN.	18	9.08	33.84	65	590.07	2,278.9

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.















Ficha Técnica

FORMATOS Pasta				9 X 10 CM. (Hex) Porcelánico Prensado		Caras
Color / Acabado				Mate		
				✓	10 Caras	
White	Gray	Black				
				✓	4 Caras	
Avalon	Nord					
				✓	16 Caras	
Blue	Green	Rose	Tobacco			

Información Técnica

PORCELÁNICO

	Separación de boquilla	4 mm	
	P.E.I.	4 (Tráfico: - Alto)	
	Tono y Textura Mezclado	Bajo	
	Resistencia al ataque químico	Conforme	A.S.T.M. C650
	Coefficiente Dinámico de Fricción	≥ 0.42 Interior Húmedo	ANSI A326.3 - 2021
	Absorción de agua	≤ 0.5 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia a la flexión	≥ 350 kg	ISO 10545-4
	Resistencia al shock térmico	Conforme	A.S.T.M. C484
	Resistencia a helada	Conforme	A.S.T.M. C1026
	Resistencia a las manchas	Conforme	A.S.T.M. C1378
	Resistencia a la abrasión	Conforme	ANSI A137

Información de Embalaje

FORMATO	Pzs./Caja	m2/Caja	Kg./Caja	Caja/Tarima	m2/Tarima	Kg./Tarima
23.2 X 26.7 CM	18	0.84	15.50	65	54.6	1,033.9