



## Technical Data Sheet

SIZES Body	24 X 48 IN. Rectified Porcelain		24 X 24 IN. Rectified Porcelain		12 X 24 IN. Rectified Porcelain		9 X 10 IN. (Hex) Pressed Porcelain	3 X 12 IN. Pressed Ceramic		
	Color / Finish	Polished	Matte	Polished	Matte	Polished	Matte	Matte	Glossy	Matte
	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	15 Faces		30 Faces		60 Faces		10 Faces	10 Faces		

## Technical Specs.

PORCELAIN		
	Grout size	1/12"
	P.E.I.	4 (Medium - Heavy Traffic)
	Shade and Texture Mixture	High
	Chemical Resistance	Compliant A.S.T.M. C650
	Water absorption	≤ 0.5 % A.S.T.M. C373
	MOHS	5 - 8 A.S.T.M. C1028
	Breaking Strength	≥ 771 lbs. ISO 10545-4
	Thermal Shock Resistance	Compliant A.S.T.M. C484
	Frost Resistance	Compliant A.S.T.M. C1026
	Stain Resistance	Compliant A.S.T.M. C1378
	Abrasion Resistance	Compliant ANSI A137

CERAMIC		
	Grout size	1/6"
	Shade and Texture Mixture	High
	Chemical Resistance	Compliant A.S.T.M. C650
	Water absorption	≤ 20 % A.S.T.M. C373
	MOHS	5 - 8 A.S.T.M. C1028
	Thermal Shock Resistance	Compliant A.S.T.M. C484
	Resistance to Cracking	Compliant A.S.T.M. C1026
	Stain Resistance	Compliant A.S.T.M. C1378

## Packaging Information

SIZE	Pcs./Box	Sq.ft./Box	Lbs./Box		Box/PAL	Sq.ft./PAL	Lbs./PAL	
			POLISHED	MATTE			POLISHED	MATTE
24 X 48 IN.	2	15.50	64.50	62.25	40	620	2,652.02	2,683.06
24 X 24 IN.	4	15.50	65.16		36	558	2,369.9	
12 X 24 IN.	8	15.50	65.74		48	744	3,348.6	
9 X 10 IN.	18	9.08	33.84		65	590.07	2,278.9	
3 X 12 IN.	22	5.33	15.65		132	703.56	2,111.4	

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.

## Dynamic Coefficient of Friction / ANSI A326.3 - 2021

SERIES	DESIGN	COLOR	BODY TYPE	FINISH	SIZE (IN)	CLASSIFICATION	DCOF
LIVIA	CALACATTA		PORCELAIN	POLISHED	24X48	INTERIOR DRY, ID	≥0.42 DCOF DRY
LIVIA	CALACATTA		PORCELAIN	POLISHED	24X24	INTERIOR DRY, ID	≥0.42 DCOF DRY
LIVIA	CALACATTA		PORCELAIN	POLISHED	12X24	INTERIOR DRY, ID	≥0.42 DCOF DRY
LIVIA	CALACATTA		PORCELAIN	MATTE	24X48	INTERIOR WET, IW	≥0.42 DCOF WET
LIVIA	CALACATTA		PORCELAIN	MATTE	24X24	INTERIOR WET, IW	≥0.42 DCOF WET
LIVIA	CALACATTA		PORCELAIN	MATTE	12X24	INTERIOR WET, IW	≥0.42 DCOF WET
LIVIA	CALACATTA		CERAMIC	MATTE	3X12	N/A (WALL TILE)	N/A (WALL TILE)
LIVIA	CALACATTA		PORCELAIN	MATTE	9X10	INTERIOR WET, IW	≥0.42 DCOF WET
LIVIA	CALACATTA		CERAMIC	GLOSSY	3X12	N/A (WALL TILE)	N/A (WALL TILE)

Cesantoni certifies that the above results were obtained in laboratory testing performed by the quality control department.

[www.cesantoni.com.mx](http://www.cesantoni.com.mx)

[contacto@cesantoni.com.mx](mailto:contacto@cesantoni.com.mx)



FO-MKT-FT REV 01



## Ficha Técnica

FORMATOS Pasta	60 X 120 CM. Porcelánico Rectificado		60 X 60 CM. Porcelánico Rectificado		30 X 60 CM. Porcelánico Rectificado		23.2 X 26.7 CM (Hex) Porcelánico Prensado	7.5 X 30 CM. Cerámico Prensado	
Color / Acabado	Pulido	Mate	Pulido	Mate	Pulido	Mate	Mate	Brillante	Mate
	✓	✓	✓	✓	✓	✓	✓	✓	✓
	15 Caras		30 Caras		60 Caras		10 Caras	10 Caras	

## Información Técnica

### PORCELÁNICO

	Separación de boquilla	2 mm	
	PEI	P.E.I.	4 (Tráfico: Medio - Alto)
	Tono y Textura Mezclado	Alto	
	Resistencia al ataque químico	Conforme	A.S.T.M. C650
	Absorción de agua	≤ 0.5 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia a la flexión	≥ 350 kg	ISO 10545-4
	Resistencia al shock térmico	Conforme	A.S.T.M. C484
	Resistencia a helada	Conforme	A.S.T.M. C1026
	Resistencia a las manchas	Conforme	A.S.T.M. C1378
	Resistencia a la abrasión	Conforme	ANSI A137

### CERÁMICO

	Separación de boquilla	4 mm	
	Tono y Textura Mezclado	Alto	
	Resistencia al ataque químico	Conforme	A.S.T.M. C650
	Absorción de agua	≤ 20 %	A.S.T.M. C373
	MOHS	5 - 8	A.S.T.M. C1028
	Resistencia al shock térmico	Conforme	A.S.T.M. C484
	Resistencia al craquel	Conforme	A.S.T.M. C1026
	Resistencia a las manchas	Conforme	A.S.T.M. C1378

## Información de Embalaje

FORMATO	Pzs./Caja	m2/Caja	Kg./Caja		Caja/Tarima	m2/Tarima	Kg./Tarima	
			PULIDO	MATE			PULIDO	MATE
60 X 120 CM	2	1.44	29.05	29.50	40	57.6	1,203.3	1,217.3
60 X 60 CM	4	1.44	29.35		36	51.84	1,075.0	
30 X 60 CM	8	1.44	31.25		48	69.12	1,518.9	
23.2 X 26.7 CM	18	0.84	15.50		65	54.6	1,033.7	
7.5 X 30 CM	22	0.49	7.1		132	64.68	957.7	

## Coeficiente dinámico de absorción / ANSI A326.3 - 2021

SERIE	DISEÑO	COLOR	PASTA	ACABADO	FORMATO (CM)	CLASIFICACIÓN	DCOF
LIVIA	CALACATTA		PORCELÁNICO	PULIDO	60X120	INTERIOR SECO	≥0.42 DCOF
LIVIA	CALACATTA		PORCELÁNICO	PULIDO	60X60	INTERIOR SECO	≥0.42 DCOF
LIVIA	CALACATTA		PORCELÁNICO	PULIDO	30X60	INTERIOR SECO	≥0.42 DCOF
LIVIA	CALACATTA		PORCELÁNICO	MATE	60X120	INTERIOR HÚMERO	≥0.42 DCOF
LIVIA	CALACATTA		PORCELÁNICO	MATE	60X60	INTERIOR HÚMERO	≥0.42 DCOF
LIVIA	CALACATTA		PORCELÁNICO	MATE	30X60	INTERIOR HÚMERO	≥0.42 DCOF
LIVIA	CALACATTA		CERÁMICO	MATE	7.5X30	N/A (WALL TILE)	N/A (WALL TILE)
LIVIA	CALACATTA		PORCELÁNICO	MATE	23.2X26.7	INTERIOR HÚMERO	≥0.42 DCOF
LIVIA	CALACATTA		CERÁMICO	BRILLANTE	7.5X30	N/A (WALL TILE)	N/A (WALL TILE)